

27.12.2022

Drawing No. 10MW-FULL-5010-LED-010

1 NO. Portable cabin 10'

### Specification

- |                                    |                                |
|------------------------------------|--------------------------------|
| - Construction type                | Transpack (flatpacked) version |
| - Construction type                | Assembled                      |
| - External cabin height            | 2591 mm                        |
| - Internal floor to ceiling height | 2340 mm                        |
| - Design of roof frame             | Standard version               |
| - Design of corner post            | Standard version               |
| - Design of floor construction     | Standard floor cross members   |
| - Parapet height                   | 870 mm above floor level (FOK) |

### Paint

- |                    |                       |
|--------------------|-----------------------|
| - Container colour | RAL 5010 Gentian Blue |
|--------------------|-----------------------|

### Internal finish

- |                           |                 |
|---------------------------|-----------------|
| - Internal finish         | Chipboard White |
| - Internal finish ceiling | Chipboard White |

### Insulation

- |                    |                     |
|--------------------|---------------------|
| - Wall insulation  | Mineral wool 60 mm  |
| - Roof insulation  | Mineral wool 100 mm |
| - Floor insulation | Mineral wool 60 mm  |

### Electrics

- |                                   |  |
|-----------------------------------|--|
| - Design of electrical connection | Including CEE countersinks, including consumer box |
| - Electrics                       | GB Standard (230V/32A/3-pin)                       |

### Design of floor construction

- |                             |                     |
|-----------------------------|---------------------|
| - Forklift pockets distance | 2050 mm             |
| - Floor panel               | Standard floorboard |
| - Floor cover               | ETERNAL 2 mm R10    |

### Description

- 1 NO. Office window with tilt and turn mechanism and roller shutter
  - External dimension: 945X1200 mm
  - Window opening clearance: 821X1076 mm
  - Parapet height: 870 mm above floor surface (FOK)
  - Roller shutter with plastic slats
  - Window glass insulated with gas filling
- 1 NO. External steel door
  - Standard dimensions (width): 875 mm
  - Light passage width: 811 mm
  - Light passage height: 2065 mm
  - Outward opening

### Electrical equipment

- 2 NO. Double socket
- 1 NO. Spur
- 1 NO. Power off switch

### Lighting

- 1 NO. Surface-mounted luminaire 30 W

27.12.2022

Drawing No.

10MW-FULL-5010-LED-010

**Note:**

Please note, if cabins with chipboard ceilings are stored uncovered as open side units or as transpacks over a longer period of time, moisture, humidity and temperature variations may cause damages and deformations of this type of ceiling boards. CONTAINEX excludes any warranty or liability for damages and consequential damages resulting from this cabin specification.

Other equipment and details according to our technical description, which we can certainly send to you on request.

Due to current developments (in particular COVID-19, availability of raw materials), delivery dates cannot be guaranteed and there may be deviations to technical specifications or fixtures and fittings.