

Drawing No. 10PU-FULL-7035-LED-010

1 NO. Portable cabin 10'

Specification

- | | |
|------------------------------------|--------------------------------|
| - Construction type | Transpack (flatpacked) version |
| - Construction type | Assembled |
| - External cabin height | 2591 mm |
| - Internal floor to ceiling height | 2340 mm |
| - Design of roof frame | Standard version |
| - Design of corner post | Standard version |
| - Design of floor construction | Standard floor cross members |
| - Parapet height | 870 mm above floor level (FOK) |
| - Neutralisation | Neutralisation |
| - Neutralisation | Neutralisation |

Paint

- | | |
|--------------------|---------------------|
| - Container colour | RAL 7035 Light Grey |
|--------------------|---------------------|

Internal finish

- | | |
|---------------------------|---|
| - Internal finish | Coated Steel Sheet White |
| - Internal finish ceiling | Plasterboard with coated steel plate, white |

Insulation

- | | |
|--------------------|---------------------|
| - Wall insulation | PU foam 60 mm |
| - Roof insulation | Mineral wool 100 mm |
| - Floor insulation | Mineral wool 60 mm |

Electrics

- | | |
|-----------------------------------|--|
| - Design of electrical connection | Including CEE countersinks, including consumer box |
| - Electrics | GB Standard (230V/32A/3-pin) |

Design of floor construction

- | | |
|-----------------------------|---------------------|
| - Forklift pockets distance | 2050 mm |
| - Floor panel | Standard floorboard |
| - Floor cover | ETERNAL 2 mm R10 |

Description

- 1 NO. Office window with tilt and turn mechanism and roller shutter
 - External dimension: 945X1200 mm
 - Window opening clearance: 821X1076 mm
 - Parapet height: 870 mm above floor surface (FOK)
 - Lockable aluminium roller shutters
 - Window glass insulated with gas filling
- 1 NO. External steel door
 - Standard dimensions (width): 875 mm
 - Light passage width: 811 mm
 - Light passage height: 2065 mm
 - Outward opening

Electrical equipment

- 2 NO. Double socket
- 1 NO. Spur
- 1 NO. Power off switch

Lighting

- 1 NO. Surface-mounted luminaire 30 W

27.12.2022

Drawing No.

10PU-FULL-7035-LED-010

Other equipment and details according to our technical description, which we can certainly send to you on request.

Due to current developments (in particular COVID-19, availability of raw materials), delivery dates cannot be guaranteed and there may be deviations to technical specifications or fixtures and fittings.