

Drawing No. 20PU-FULL-7035-LED-010

1 NO. Portable cabin 20'

### Specification

- Construction type	Transpack (flatpacked) version
- Construction type	Assembled
- External cabin height	2591 mm
- Internal floor to ceiling height	2340 mm
- Design of roof frame	Standard version
- Design of corner post	Standard version
- Design of floor construction	Standard floor cross members
- Parapet height	870 mm above floor level (FOK)

### Paint

- Container colour	RAL 7035 Light Grey
--------------------	---------------------

### Internal finish

- Internal finish	Coated Steel Sheet White
- Internal finish ceiling	Plasterboard with coated steel plate, white

### Insulation

- Wall insulation	PU foam 60 mm
- Roof insulation	Mineral wool 100 mm
- Floor insulation	Mineral wool 60 mm

### Electrics

- Design of electrical connection	Including CEE countersinks, including consumer box
- Electrics	GB Standard (230V/32A/3-pin)

### Design of floor construction

- Forklift pockets distance	2050 mm
- Floor panel	Standard floorboard
- Floor cover	ETERNAL 2 mm R10

### Description

- 2 NO. Office window with tilt and turn mechanism and roller shutter
  - External dimension: 945X1200 mm
  - Window opening clearance: 821X1076 mm
  - Parapet height: 870 mm above floor surface (FOK)
  - Lockable aluminium roller shutters
  - Window glass insulated with gas filling
- 1 NO. External steel door
  - Standard dimensions (width): 875 mm
  - Light passage width: 811 mm
  - Light passage height: 2065 mm
  - Outward opening

### Electrical equipment

- 2 NO. Double socket
- 1 NO. Spur
- 1 NO. Power off switch

### Lighting

- 2 NO. Surface-mounted luminaire 30 W

28.12.2022

Drawing No.

20PU-FULL-7035-LED-010

Other equipment and details according to our technical description, which we can certainly send to you on request.

Due to current developments (in particular COVID-19, availability of raw materials), delivery dates cannot be guaranteed and there may be deviations to technical specifications or fixtures and fittings.